3.3.4.4 District Specific Standards Summary

The table below states the building forms allowed in each zone district. The table also summarizes the maximum number of structures allowed per Zone Lot, which is stated in more detail in Section 1.2.3.5 (Number of Uses and Structures Allowed per Zone Lot).

See also Division 1.4, Building Form Standards - General Provisions, for additional standards related to initial assignment of building form standards to new and existing structures and for rules governing combining or changing building forms. <u>Building Connectors between two detached structures</u> shall follow the standards provided in Section 1.4.5.

Note: The table below is intended to show that CPD proposes to combine Other Detached Accessory Structures with Detached Garages and Detached Accessory Structures into a single building form called General Detached Structure. The red boxes under General Detached Structure for the Commercial Corridor, Mixed Use, and Main Street districts show that those standards are being moved to the combined building form. We'll also add a new building form for Minor Detached Structures.

Suburban (S-) Neighborhood Context Zone Districts		Max Number- of Detached Accessory Structures- per Zone Lot	Building Forms				
			Detached Accessory Dwelling Unit	Detached-Garage-General Detached Structure	Other Detached Accessory Structures	Minor Detached Structures	Detached- Accessory- Structures
Maximum numb structures per Zo	er of detached accessory one Lot		One per Primary Dwell- ing Unit*	No max*		Option A: No max Option B: No max	
	S-SU-A, -D, -F, -Fx, -I, -lx	no max*	•	-		•	
Single Unit (SU)	S-SU-A1, -D1, -F1, -F1A, F1x, -I1, -I1x	no max*		•		•	
Row House_(RH)	S-RH-2.5	no max*					
Multi Unit (MU)	S-MU-3, -5, 8, 12, 20	no max*	•	•	•	-	
Commercial Corridor (CC)	S-CC-3, -3x, -5, -5x	no max	-	•		•	-
	S-MX-2x	no max		•		•	
Mixed Use (MX)	S-MX-2, -3, -5, -8, -12	no max		•			
ng	S-MX-2A, -3A, -5A, -8A, -12A	no max		•			
Main Street (MS)	S-MS-3, -5	no max	•	•		•	•

Correct
omitted boxes
where Detached
Accessory Dwellin
Unit form is
allowed

^{■ =} Allowed □ = Allowed subject to limitations

^{*}One per dwelling unit for structures with vehicle access doors, See Section 1.2.3.5.

Correct om

DETACHED ACCESSORY DWELLING UNIT

nitte	d zone districts				
		S-SU-A1, -D1, -F1, -F1A, -F1x, -I1, I1x			
	HEIGHT	Option A: 1-story*	Option B: 2-stories*	S-RH-2.5	<u>All</u> S-MU -3, -5, -8, -12, -20 , CC, MX, MS
Α	Stories (max)	1	2	2	2
Α	Feet (max)	17'	24′	24′	24′
В	Bulk Plane Vertical Height at Side Interior and Side Street Zone Lot Line	10′	10′	10′	na
С	Bulk Plane Slope from Side Interior Zone Lot Line	45°	45°	45°	na

		S-SU-A1, -D1, -F1, -F1A, -F1x, -l1, l1x			
9	SITING	Option A: 1-story*	Option B: 2-stories*	<u>A</u> S-RH-2.5	<u>II</u> S-MU -3, -5, -8, -12, -20 , CC, MX, MS
-	SETBACKS				
l	Location of Structure	Located in the rear 50% of the zone lot depth			
D i	Side Interior and Side Street for lots 25' wide or less (min)	3′	3′	3′	3′
	Side Interior and Side Street for lots greater than 25' wide and less than 62' wide (min)	5'	5'	5′	5′
D	Side Interior and Side Street for lots 62' wide or greater (min)	7.5'	7.5'	5′	5′
_	Rear (min)	10'	20'	5′	5′
4	Additional Standards	See Maximum Building Coverage per Zone Lot in the Primary Structure build ing form table.			
1	Maximum Building Coverage				
PARKING					
_	Vehicle Access	From Alley; or Street access allowed when no Alley present See 3.3.7.6 for exceptions			lley present
	S-SU-A1, -D1, -F1, -F1A, -F1x, -I1, I1:		F1x, -I1, I1x	All S-RH -2.5 ,	
		Opti	S- MU,- 3, -5, -8, -12,		
					-20 CC, MX,
	DESIGN ELEMENTS	7,000 st	or Less	Greater than 7,0	00 sf <u>MS</u>
E	BUILDING CONFIGURATION				
E	Building Footprint (max)	864 sf sf	per unit	1,000 sf sf per u	nit 1,000 sf per unit
	Limitation on Gross Floor Area of the Accessory Dwelling Unit Use	See Section 11.8			
F	Rooftop and/ or Second Story Decks	Not allowed - See Section 3.3.5.2			

USES	All S-SU; S-RH-2.5; All S-MU <u>, CC, MX, MS</u>
	An Accessory Dwelling Unit use must be concurrently permitted and ap-
	proved for occupancy in this building form. The Accessory Dwelling Unit use
	may be combined with other uses Accessory to Primary Residential Uses.
	See Division 3.4 for permitted Uses Accessory to Primary Residential Uses.

^{*}Standards in the "Option A" column may not be combined with standards in the "Option B" column. For example, If using Option B height standards to construct a two-story structure, the structure must also follow the Option B siting standards that require a minimum 20' rear setback.